

# 15.0" Daylight Infinity Display

## Electrical Description

### Display Characteristics:

Type: 15.0" Active Matrix TFT  
Dot Number: 1024 x 768 Pixels  
Dot Pitch: 0.297mm  
Response Time: 20ms Average- Typical  
Contrast Ratio: 300:1 Min.  
Brightness / Light Intensity: Enhanced to 500cd/m<sup>2</sup> (Nits)- Typical  
Viewing Angles (at CR>10): 70° Left/Right, 60° Up & 65° Down  
Backlight Life: 50,000 Hours- Typical  
Colour Depth: 16.7 Million (Depending on Graphics Card)

### Dimming Circuit:

Range: Full on to Black

### Analog RGB Input:

Analog Interface: 75 Hz Maximum Analog Bandwidth  
0.5V to 1.0V Analog Input Range  
Sync-on-Green (-ve) 0.3V

### Synchronisation Range:

Horizontal Scan: 31.469-60.023kHz\*  
Vertical Scan: 56.25-75.029 Hz\*

*\*Depending on resolution*

### Resolutions:

VESA Support for: 1024 x 768 XGA\*  
800 x 600 SVGA  
640 x 480 VGA

*\*Recommended for optimised resolution*

### Active Display Area:

Active Display Area: 304.4mm x 228.6mm

### Input Voltage:

DC Input: 12.1V DC Regulated  
*Via external power supply - Refer to ordering codes...*

### Power Consumption:

2.4 A (30 W) Max.

### Environmental:

\*Operating Temp: 32 to +131°F / 0 to +55°C  
Storage Temp: -4 to +140°F / -20 to +61°C  
Operating Humidity: 30% to 90% (Non-Condensing)  
Storage Humidity: 10% to 90% (Non-Condensing)  
Shock: 10g, 11msec ½ Sine Wave  
Vibration: +/-1mm, 2 to 13Hz:0.7g 13 to 100Hz

*\*We DO NOT recommend routine operation @ extreme temperatures.*

## Mechanical Description

### Construction:

Finish: Gray Fine Textured Semi Gloss  
Powder Coat  
Housing: Preformed Aluminium  
Sealing: Waterproof NEMA 6 / IP67  
Toughened Safety Glass : Bonded, Contrast Enhancing,  
Optically Coated and Polarized  
Ventilation: Convection

### Mounting Style:

Surface (mm): Surface Mounted with 1 23/32" (43.66)  
Protruding and Fastened with 4  
Mounting Studs  
Panel Cut-Out Size (mm): 13 9/16" (344.49) x 10 7/16" (265.11)

### Dimensions:

15 3/8" (390.53) W x  
Display: 11 23/32" (297.66) H x  
2 63/64" (75.80) D

### Weight:

Weight (kg): 10.2 lbs (4.7)

### Input Connectors: (rated @ NEMA 6 / IP67)

RGB Signal: 15 Pin Male Connector  
Power: 2 Pin Male Circular

### Menu Controls:

Via Front Mounted Buttons: OSD Picture Features:  
Size, Position, Colour & Auto-Tune

## Approvals / Warranty

**Compliance:** CE; CISPR22 / EN 55022

FCC Part 15 Section 15.109

**Limited Warranty:** 2 Year

## Ordering Codes

### Configuration:

15.0" Daylight Display: 17-1510  
*Please select external power supply from list below...*

### External Power Supply:

External 115/230V: 00-0301  
External 12V DC: 00-0302  
External 24V DC: 00-0303

### Shipping:

Carton Size (cm): 21" (53) W x 20" (51) H x 10" (25) D  
Weight (kg): 26.0 lbs (12)

Canadian  
Headquarters: **Nauticomp Inc.**  
8 Callaghan Road  
Lindsay, Ontario,  
Canada, K9V 4R4.  
p: +1 705-328-2992  
f: +1 705-328-2990

United Kingdom: **Nauticomp European Distribution**  
CA Clase  
2 Mornington Place, Waterberry Drive,  
Waterlooville, Hants, PO7 7XX  
p: +44 2392 247920  
f: +44 2392 261959

United States: **Nauticomp International**  
1200 NE 7th Avenue  
Fort Lauderdale, Florida  
United States 33304.  
p: +1 954 235 4875  
f: +1 705-328-2990

URL: [www.nauticomp.com](http://www.nauticomp.com) E-Mail: [sales@nauticomp.com](mailto:sales@nauticomp.com)

Due to a policy of continuous product development NAUTICOMP reserves the right to change specifications and descriptions without prior notification. All trade marks acknowledged.

Due to a policy of continuous product development NAUTICOMP reserves the right to change specifications and descriptions without prior notification. All trade marks acknowledged.