

# Titan Commercial Grade LED Display Installation Guide

## Part 1: Display Mounting

### Step 1

Install 'Ram mount' bracket on rear of display using the four VESA mount PEMS.

### Step 2

Attach 'Ram mount' arm to bracket by unscrewing the giant wing-nut and placing over pedestal ball.

## Pedestal Mount



## Bracket Mount

### Step 1

Attach Mounting Brackets to display using the 4 supplied screws.

### Step 2

Mount display to dash as desired.




## Part 2: Connecting the Display to Power

### Step 1

Connect input voltage wires (1) from vessels power supply (i.e. 12, 24, 36 VDC or 110 VAC as specified on order) to Nauticomp power supply. Connect **red** wire to positive input terminal and the **black** wire to negative input terminal. Tighten connectors securely.

### Step 2

Connect the wires (2) from the display to the power supply. Connect red wire to positive output terminal and the black wire to



## Part 3: Connecting Cables to the Display

POWER OUTPUT FROM THE PROVIDED NAUTICOMP POWER SUPPLY IS TO BE 12.1VDC. PLEASE DOUBLE CHECK BEFORE CONNECTING TO THE DISPLAY FOR THE FIRST TIME.

PLEASE NOTE: ALWAYS CONNECT ALL VIDEO INPUT CABLES BEFORE CONNECTING THE POWER

### Step 1

Press in Power connector until secure, Press in DVI, VGA, S-Video & Composite connectors then screw in mounting screws.

### Step 2

Gently pull all cables to insure that they are connected securely.

POWER

DVI

VGA

S-VIDEO

COMPOSITE

AUDIO



For Any assistance with the operation of your new Titan Series Display, Please call us @ 705-328-2992

See reverse for Quick Reference

**NAUTICOMP**